
TUNGSTEN FRESNEL FILMGEAR



Tungsten Fresnel 12kW/10kW Studio

L12010TF

## ■ DIMENSIONS (mm)



# Tungsten Fresnel 12kW/10kW Studio

# ■ SPECIFICATIONS

Product No.	L12010TF
Capacity	12,000W / 10,000W
Lamp Bulb Voltage	220V
Fresnel Lens Ø	450mm (17-3/4 in.)
Weight (without barndoor)	34.0 kg
Weight (with barndoor)	38.9 kg
Lamp Type	12kW/10kW SE 3200 °K
Lamp Holder	G38
Stirrup	28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / 23
Max. Surface Temp.	220 °C
Max. Ambient Temp.	45 ℃
Min. Distance to Illuminated Object	10 m
Min. Distance to Flammable Object	2 m
Operating Range	30° - 0° - 30°

#### **■ PHOTOMETRIC DATA**

12000111						
12000W Bulb	Distance	10m	1	15m		20m
Spot (120)						
Spot (12°) Lux		16160	718	32	40	)40
Beam Ø	7	2.10 m	3.15	m	4.2	0 m
Flood (62°)						
Lux		2409	107		-	02
Beam Ø	1	2.02 m	18.03	3 m	24.0	03 m

10000W Bulb	Distance	10m	15m	20m
Spot (13°) Lux Beam Ø		13377 2.28 m	5947 3.42 m	3344 4.56 m
Flood (60°) Lux Beam Ø		2016 11.55 m	896 17.32 m	504 23.09m

#### ■ PACKAGE CONTENT

Aluminium Lamp Housing with 4-leaf Rotatable Barndoor with Safety Wire
Ø 450mm (17-3/4 in.) Fresnel Lens
G38 Lampholder
Stirrup with 28mm (1-1/8 in.) Spigot
3-core Cable 4m (13 ft.)
On/Off Switch

## ACCESSORIES

4-leaf Rotatable Barndoor
Filter Frame
Set of 4 Scrims Ø 533mm (21 in.):
Full Single Scrim
Full Double Scrim
Half Single Scrim
Half Double Scrim
Carrying Bag for Ø 533mm (21 in.) Scrim Set
Safety Wire